119	(iii) having an unladen dry weight of 6,500 pounds or less;
120	(iv) having a maximum seat height of 50 inches when measured at the forward edge of
121	the seat bottom; and
122	(v) having a steering wheel for control.
123	(b) "Full-sized all-terrain vehicle" does not include:
124	(i) all-terrain type I vehicle;
125	(ii) a utility type vehicle;
126	(iii) a motorcycle; or
127	(iv) a snowmobile as defined in Section 41-22-2.
128	(20) "Gore area" means the area delineated by two solid white lines that is between a
129	continuing lane of a through roadway and a lane used to enter or exit the continuing lane
130	including similar areas between merging or splitting highways.
131	(21) "Gross weight" means the weight of a vehicle without a load plus the weight of
132	any load on the vehicle.
133	(22) "Heavy vehicle" means any $\mathbf{\hat{H}} \rightarrow [\mathbf{motor}] \leftarrow \mathbf{\hat{H}}$ vehicle:
134	(a) with a gross vehicle weight rating of 26,001 pounds or greater; or
135	(b) that has an air braking system.
136	[(22)] (23) "Highway" means the entire width between property lines of every way or
137	place of any nature when any part of it is open to the use of the public as a matter of right for
138	vehicular travel.
139	[(23)] (24) "Highway authority" has the same meaning as defined in Section 72-1-102.
140	[(24)] (25) (a) "Intersection" means the area embraced within the prolongation or
141	connection of the lateral curblines, or, if none, then the lateral boundary lines of the roadways
142	of two or more highways which join one another.
143	(b) Where a highway includes two roadways 30 feet or more apart:
144	(i) every crossing of each roadway of the divided highway by an intersecting highway
145	is a separate intersection; and
146	(ii) if the intersecting highway also includes two roadways 30 feet or more apart, then
147	every crossing of two roadways of the highways is a separate intersection.
148	(c) "Intersection" does not include the junction of an alley with a street or highway.
149	[(25)] (26) "Island" means an area between traffic lanes or at an intersection for control

inspection certificates.

367

368

369

370

371

372

373

374

375

376

377

378

(c) \$20 or less for 4-wheel drive, split axle, and any motor vehicles that necessitate disassembly of front hub or removal of rear axle for inspection[-]; or
(d) Ĥ→ [\$85] \$50 ←Ĥ or less for a heavy vehicle.
(5) A safety inspection station may return unused safety inspection certificates in a

quantity of 10 or more and shall be reimbursed by the division for the cost of the safety

- (6) (a) Upon receiving notice of the suspension or revocation of a safety inspection station permit and after the conclusion of any adjudicative proceedings upholding the suspension or revocation, the safety inspection station permit holder shall immediately terminate all safety inspection activities and return all safety inspection certificates and the safety inspection station permit to the division.
 - (b) The division shall issue a receipt for all unused safety inspection certificates.